



INSPECTION REPORT

PARAGLIDERS RESCUE SYSTEMS | EMERGENCY PARACHUTE

Inspection report number: **EP_124.2015**

SAMPLE DATA

Manufacturer name: **Companion / EVOTEC**
Representative: **Peter Mack**
Street: **Munkacsy M. Str. 8**
Post code / place: **7695 Mecseknadasd**
Country: **Hungary**
Model name: **SQR**
Model size: **120**
Manufacturer max load [kg]: **120**
Manufacturers serial number flight (EP1, EP2, EP4, EP6): **0004**
Manufacturers serial number load (EP3, EP5): **0044**

Date of reception: **06.02.2015**
Date of reception: **06.02.2015**

Date of issue: **29.10.2015**
Place of declaration: **Villeneuve**
Director management: **Alain Zoller**

Signature:

Air Turquoise SA, having thoroughly assessed the sample mentioned hereunder, declare it was found conform with all requirements defined by the following directives:

EN 12491 | 2001 and LTF NFL II 91/09 chapter 6 Paraglider rescue systems
LTF Ref chapter: 6.1.1 to 6.1.19, exclusion 6.1.10

Present declaration's scope only extends to the conformity of a given sample, on a given date and in a given place – as mentioned here above.

This inspection report contain the following test and is complet with the test report number EP1 to EP6

TESTS	RESULTS	INSPECTORS	PLACES	DATES
1. Deployment system strength test (inner container)				
Minimum 700 N strength required during min 10 [s]:	POSITIVE	AZ	Villeneuve	23.02.2015
2. Descent rate and stability test - ref. A and B				
Sink rate EN standard	POSITIVE	GB	Villeneuve	12.02.2015
Sink rate LTF standard	POSITIVE	GB	Villeneuve	12.02.2015
Speed opening	POSITIVE	GB	Villeneuve	12.02.2015
Stability	POSITIVE	GB	Villeneuve	12.02.2015
3. Strength test opening shock				
Test 1 40 [m/s]	POSITIVE	AZ	Illarsaz	14.04.2015
Test 2 40 [m/s]	POSITIVE	AZ	Illarsaz	14.04.2015
Test 3 40 [m/s]	POSITIVE	AZ	Illarsaz	14.04.2015
4. Interaction and stability test (piloted) - ref. C				
the emergency parachute is deployed from a paraglider in normal straight flight.	N/A	n/a	n/a	x
the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres.	N/A	n/a	n/a	x
the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.	N/A	n/a	n/a	x
5. Connecting strap				
Minimum load capacity of 2400 [daN]	POSITIVE	AZ	Villeneuve	18.02.2015
6. Measurement				
According to manufacturer user manual	POSITIVE	AZ	Villeneuve	17.02.2015

This declaration must not be reproduced in part without the written permission of AIR TURQUOISE SA.



Deployment system strength

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 1

Test report number: **EP_124.2015**

SAMPLE DATA

Manufacturer name: **Companion / EVOTEC**
Representative: **Peter Mack**
Street: **Munkacsy M. Str. 8**
Post code / place: **7695 Mecseknadasd**
Country: **Hungary**
Rescue systems manufacturers name: **SQR**
Rescue systems manufacturers Size: **120**
Rescue systems manufacturers max load (kg): **120**
Manufacturers serial number flight : **0004**
Date of sample received: **06.02.2015**
Place of test: **Villeneuve**
Date of test: **23.02.2015**
Directive: **EN 12491 | 2001 chapter 5.3.2 and LTF 91/09 chapter 6**
Inspector: **Alain Zoller**

Results: **POSITIVE**

Signature:

ATMOSPHERE AGL

[C°] **21.1**
RH [%] **31**
[hPa] **1011.9**

The deployment system is loaded at min 700 [N] during 10 secondes min. The deployment system is loaded until breaking. Each component is tested.

RESULTS

Minimum strength required during min 10s [kN]: **700.00**

Strength of 700 N duration each components no1 [s]: 1 **0.52**

Strength of 700 N duration each components no2 [s]: 2 **12.2**

Strength of 700 N duration each components no3 [s]: 3 **N/A**

Uncertainty 95% [kN]: **0.017**

INSPECTION RESULTS MINIMUM Time [s]: **0.5**

Max strength components [kN]:

Max strength components no1 [kN]: 1 **0.849**

Max strength components no2 [kN]: 2 **1.516**

Max strength components no3 [kN]: 3 **N/A**

Uncertainty 95% [kN]: **0.017**

Max strength [kN]: **0.849**



Deployment system strength


PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 1


Test report number: EP_124.2015

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Deployment system strength test	Load Cell (axial)	11.06.2016	Burster / MTS	8431-10000	1185483
Deployment system strength test	USB interface	11.06.2016	Burster / MTS	9205-V001	10000469
Deployment system strength test	Winch	06.01.2017	Arwin	300/600	n/a
Weather	Geos n° 11 Skywatc	08.05.2017	JDC elec.	Geos n° 11	22


Min strength 10 sec. each components 1



Min strength 10 sec. each components 2



Min strength 10 sec. each components 3






Descent rate and stability test - ref. A and B

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_124.2015

SAMPLE DATA

Manufacturer name: Companion / EVOTEC
Representative: Peter Mack
Street: Munkacsy M. Str. 8
Post code / place: 7695 Mecseknadasd
Country: Hungary
Rescue systems manufacturers name: SQR
Rescue systems manufacturers Size: 120
Rescue systems manufacturers max load [kg]: 120
Manufacturers serial number flight : 0004
Date of sample received: 06.02.2015
Place of test: Villeneuve
Date of test: 12.02.2015
Directive: EN 12491 | 2001 chapter 5.3.4 and 5.3.3 and LTF 91/09 chapter 6
Inspector: Alain Zoller
Signature: 

ATMOSPHERE AGL	Test no1	ATMOSPHERE AGL	Test no2
[C°]	1	[C°]	4
RH [%]	79	RH [%]	79
[hPa]	976	[hPa]	978.6
Wind [m/s]	0.1	Wind [m/s]	0.1

The rescue system is dropped from a paraglider in straight flight at 8 [m/s] +-1 [m/s]. The paraglider is released as the rescue system begins to open, minimum 100 [m] descent. Wink link 200 [N] is used to measure the speed opening.

RESULTS	EN	LTF
Sink rate results:	POSITIVE	POSITIVE
Stability results:	POSITIVE	POSITIVE
Speed opening results:	POSITIVE	POSITIVE
Max sink rate test requirements [m/s]	5.50	6.80
Sink rate test 1 [m/s] 1	5.30	5.30
Sink rate test 2 [m/s] 2	5.37	5.37
Behavior during descent		
Stability test 1 1	Stable	Stable
Stability test 2 2	Stable	Stable
Requirement time from the instant of free drop until a load of 200 [N] is sustained [s]	5.00	5.00
Speed opening test 1 [s]	4.15	4.15
Speed opening test 2 [s]	3.31	3.31

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Deployment system strength test	Weak links	2030	Tost	n/a	n/a
Descent rate and stability test	Line 30 meters	2020	Air Turquoise	n/a	n/a
Descent rate and stability test	Camecorder	2020	CANON	Legria HF G10	463440300907
Weather	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22



Descent rate and stability test - ref. A and B

PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_124.2015

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass of differences from ICAO standard atmosphere

$$m_{corr} := m_{dec} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Sink rate test 1

Ground level atmospheric pressure at test location: (p)	976 [hPa]	RH [%]	79
ICAO standard atmospheric pressure at MSL: (p ₀)	1013.25 [hPa]	Wind [m/s]	0.1
Ground level temperature at the test location: (T)	1 [C°]		
	274.15 [°K]		
ICAO standard temperature at MSL: (T ₀)	15 [C°]		
	288.15 [°K]		
Total weight in flight: (m _{dec})	120 [kg]		
Corrected mass: (m _{corr})	121.49 [kg]		
Corrected mass with uncertainty: (m _{corr})	122.39 [kg]		
Time when pilot release rescue	41.76		
Time when weak link broke	45.76		
Speed opening (sec.):	4.15 [s]		
Time boil touch	30.1		
Time pilot touch	35.92		
Time between boil touch and pilot touch (30m)	5.67 [s]		
Sink rate:	5.2963 [m/s]		
Behaviour:	Stable		
Inspector:	GB		
Date of test :	12.02.2015		

Sink rate test 2

Ground level atmospheric pressure at test location: (p)	978.6 [hPa]	RH [%]	79
ICAO standard atmospheric pressure at MSL: (p ₀)	1013.25 [hPa]	Wind [m/s]	0.1
Ground level temperature at the test location: (T)	4 [C°]		
	277.15 [°K]		
ICAO standard temperature at MSL: (T ₀)	15 [C°]		
	288.15 [°K]		
Total weight in flight: (m _{dec})	120 [kg]		
Corrected mass: (m _{corr})	120.50 [kg]		
Corrected mass with uncertainty: (m _{corr})	121.40 [kg]		
Time when pilot release rescue	34.48		
Time when weak link broke	37.64		
Speed opening (sec.):	3.31 [s]		
Time boil touch	1.18		
Time pilot touch	6.92		
Time between boil touch and pilot touch (30m)	5.59 [s]		
Sink rate:	5.3721 [m/s]		
Behaviour:	Stable		
Inspector:	GB		
Date of test :	12.02.2015		



Descent rate and stability test - ref. A and B


PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 2

Test report number: EP_124.2015

WINK LINKS 1

Picture



WINK LINKS 2

Picture





Strength test opening shock

PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 3

Inspection report number: EP_124.2015

TEST SAMPLE DATA

Manufacturer name: Companion / EVOTEC
Representative: Peter Mack
Street: Munkacsy M. Str. 8
Post code / place: 7695 Mecseknadasd
Country: Hungary
Rescue systems manufacturers name: SQR
Rescue systems manufacturers Size: 120
Rescue systems manufacturers max load [kg]: 120
Manufacturers serial number load : 0044
Date of sample received: 06.02.2015
Place of test: Illarsaz
Date of test: 1 | 2 | 3: 14.04.2015 14.04.2015 14.04.2015
Directive: EN 12491 | 2001 chapter 5.3.5 and LTF 91/09 chapter 6
Inspector: Alain Zoller
Results: POSITIVE

Signature:

ATMOSPHERE AGL	Test no1	Test no2	Test no3
[C°]	13.5	13.5	13.5
RH [%]	60	60	60
[hPa]	985.4	985.4	985.4
Wind [m/s]	0.2	0.2	0.2

The drop test device is accelerated to a straight line velocity of 40 m/s. Speed of opening must be less than 5 seconds and shock not exceeded 15g.

RESULTS

Speed of opening in max 5 secondes

Speed of opening test 1 [s] POSITIVE
Speed of opening test 2 [s] POSITIVE
Speed of opening test 3 [s] POSITIVE
Uncertainty 95% [s] 0.15

Sample statut after shock

Strength test 40 m/s opening shock 1 POSITIVE
Strength test 40 m/s opening shock 2 POSITIVE
Strength test 40 m/s opening shock 3 POSITIVE
Uncertainty 95% [m/s] 1.73

Wink link statut after shock

Wink link test 1 POSITIVE
Wink link test 2 POSITIVE
Wink link test 3 POSITIVE
Uncertainty 95% [%] 10



Strength test opening shock

PARAGLIDERS RESCUE SYSTEMS
TEST REPORT EP 3

Test report number: EP_124.2015

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Strength test 41 m/s opening shock	Helicopter	Air-Glacier	Air-Glacier	Air-Glacier	Air-Glacier
Strength test 41 m/s opening shock	Weight	2017	Air Turquoise	n/a	n/a
Strength test 41 m/s opening shock	Wink links	2020	Tost	n/a	n/a
Strength test 41 m/s opening shock	Camecorder	2017	CANON	Legria HF G10	463440300907
Weather	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22

WINK LINKS 15g 1





Interaction and stability test (piloted) - ref. C

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 4

Test report number: EP_124.2015

TEST SAMPLE DATA

Manufacturer name: Companion / EVOTEC
Representative: Peter Mack
Street: Munkacsy M. Str. 8
Post code / place: 7695 Mecseknadasd
Country: Hungary
Rescue systems manufacturers name: SQR
Rescue systems manufacturers Size: 120
Rescue systems manufacturers max load (kg): 120
Manufacturers serial number flight : 0004
Date of sample received: 06.02.2015
Place of test: x
Date of test: x
Directive: EN 12491 | 2001 chapter 5.3.6 and LTF 91/09 chapter 6
Inspector: x

Results: N/A

Signature:

ATMOSPHERE AGL	Test no1	ATMOSPHERE AGL	Test no2
[C°]	x	[C°]	x
RH [%]	x	RH [%]	x
[hPa]	x	[hPa]	x
Wind [m/s]	x	Wind [m/s]	x

TEST RESULTS

- a the emergency parachute is deployed from a paraglider in normal straight flight. N/A
- b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. N/A
- c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres. N/A



Connecting strap

EP PARAGLIDERS RESCUE SYSTEMS

TEST REPORT EP 5

Test report number: EP_124.2015

TEST SAMPLE DATA

Manufacturer name: Companion / EVOTEC
Representative: Peter Mack
Street: Munkacsy M. Str. 8
Post code / place: 7695 Mecseknadasd
Country: Hungary
Rescue systems manufacturers name: SQR
Rescue systems manufacturers Size: 120
Rescue systems manufacturers max load (kg): 120
Manufacturers serial number load : 0044
Date of sample received: 06.02.2015
Place of test: Villeneuve
Date of test: 18.02.2015
Directive: LTF 91/09 chapter 6
Inspector: Alain Zoller

Results: POSITIVE

Signature:

ATMOSPHERE AGL


[C°] 22.3
RH [%] 29
[hPa] 1025.8

The connecting strap is loaded at min 2400 [daN] and must not break.

RESULTS [daN]

Minimum required load 2400
Load capacity 1 2583
Uncertainty 95% 42
Max STRENGTH 2540.9

GRAPHIQUE Connecting strap



Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Strap	Load Cell (axial)	11.06.20	Althen	SHK-D-3	20562
Atmosphere	Geos n° 11 Skywatch	08.05.20	JDC elec.	Geos n°	22

Measurement 50 N

EP PARAGLIDERS RESCUE SYSTEMS

MEASUREMENT REPORT EP 6

Teste report number: EP_124.2015

TEST SAMPLE DATA

Manufacturer name: Companion / EVOTEC
Representative: Peter Mack
Street: Munkacsy M. Str. 8
Post code / place: 7695 Mecseknadasd
Country: Hungary
Rescue systems manufacturers name: SQR
Rescue systems manufacturers Size: 120
Rescue systems manufacturers max load (kg): 120
Manufacturers serial number flight : 0004
Place of test: Villeneuve
Date of measurement: 17.02.2015
Directive: EN 12491 | 2001 chapter and LTF 91/09 chapter 6
Inspector: Alain Zoller

According to manufacturer user manual **POSITIVE**

Signature:



ATMOSPHERE AGL

[C°] 21.1
RH [%] 47.7
[hPa] 1009.3

The rescue system lines are measured with 50[N] of tension. Center line and all types of mains lines are measured from attach point base until end of riser. Canopy dimensions are not measured. The rescue system is weighed with pod. Dimentions are compare with users manual.

RESULTS

Center Line (average) [mm] 5620
Main Line (average of 5 pcs) 1 [mm] 5260
Main Line (average of 5 pcs) 2 [mm] n/a
Tolerance [mm] 25
Number of center lines: 1
Number of main lines 1: 14
Number of main lines 2: n/a
Weight [grame] 1438

Involved test	Item	Validity	Manufacturer	Type nr.	S/N
Line length measurements	laser distance meter	07.04.2017	Leica	DISTO D3a BT	911110352
Atmosphere	Geos n° 11 Skywatch	08.05.2017	JDC elec.	Geos n° 11	22